

Product Information

5 Liter opti rib® can HDPE, 250 g, DIN 51/55, UN

Art.-Nr.	722 005 52	722 005 57
Ident.-Nr.:	2000098963	2000086202
Colour:	natural	blue

Description
with blow-moulded Handle
non-residue emptying
label field on both sides
stackable
with visibility strip (optional)

Dimension:

Length	190 mm ±3mm
Width	145 mm ±3mm
Height	251 mm ±3mm
Weight	250 g ± 5 g
Overflow capacity	5,35 Liter
Neck Opening	Ø 44,5 mm -0,5mm

Label field:

Height	145,0 mm
Width	140,0 mm

Imprints:

Front	Back	Bottom
Scale 1 – 4 l	PE-Recycling symbol	Kautex
UN approval	Braille imprint	5 Liter
Braille imprint		Mould No.
Production date		

Packing units 16 pieces / package 2 package / layer 5 layers / palett
Amount on pallet 160 pieces 352 pieces Euro pallet (1200 x 800 mm)
Height of pallet 1321 mm 2701 mm

Approval: 3H1/X1.9/250/ .. /D/ BAM 11872-KWA

This can is certified for the filling of dangerous materials according to the European Dangerous Goods Regulations. Certification applies to the following substances:

Model substance	Density
Water	1,9 g /cm ³
Wetting Agents	1,2 g /cm ³
Acetic Acid	1,4 g / cm ³
n-Butyl Acetate	1,2 g / cm ³
White spirit	1,2 g / cm ³
Nitric Acid 55 %	1,2 g /cm ³

The UN-certification is only valid with approved closures. (see details in the certificate of approval)

approved closures	drawing no.	raw material	supplier
51-OV	V 5100-OV	L	LT Kunststofftechnik GmbH & Co. KG
51-OV-E	V 5101-OV	L	LT Kunststofftechnik GmbH & Co. KG
SK 51/16 OV	V5115	O	Kunststoff-Technik Helmstedt GmbH
SK 51/16 OV SCC EV	V5123	O	Kunststoff-Technik Helmstedt GmbH
SK 55/27 MAB MDR	ENG-00-008832 e	I	BERICAP GmbH & Co. KG
SK 55/27 MAB MDR MPV D15	ENG-00-014431 b	L	BERICAP GmbH & Co. KG
SV 51-OV-A-PE	SV 51-OV-A-PE	L	VerschlussSysteme Chadrysiak
SV 51-OV-A VE/PE	SV 51-OV-A VE/PE	L	VerschlussSysteme Chadrysiak

No responsibility is taken for the correctness of this product information. This document is subject to change without prior written notice.